



HOTCHKISS AIR SUPPLY

Heating, Ventilating & Air Movement Equipment

Hasflex PVC Flexible Ducting



HASFLEX MP PVC Grey Reinforced Flexible Ducting

Application

The grey reinforced ducting is manufactured for the HVAC market and industrial purposes. It is suitable for all normal ventilation and air conditioning systems, including high pressure, and successfully withstands constant bending or flexing.

Construction

A fully flexible polyester reinforced PVC coated ducting with an encapsulated high tensile steel wire helix.

Advantages

- Supplied in standard 6 metre length, compressed to 0.8 metre.
- Individually packaged.
- Easy to connect to either round or oval ducting.
- No special tools required for cutting or fixing.



Technical data

Diameter range (mm)	80-610
Temperature range C	- 10/+75
Maximum air velocity	30m/sec
Max. Positive working pressure	3000 Pa
Standard length	6 metre
Packing	Individual box of 0.8 metre
Clamping	Hasflex Lightning band, Stainless Steel Clamps, Nylon Clamps or Quick Release Clamps.

Head Office Heath Mill Road, Wombourne, Wolverhampton, West Midlands WV5 8AP

Head Office 01902 895161
Wolverhampton Branch 01902 895161
Hailsham Branch 01323 847910

London Branch 020 8803 9622
Rochester Branch 01634 672730
Stoke Branch 01782 274000

Bury Branch 0161 796 8226
Nottingham Branch 0115 979 4527
Eastleigh Branch 02380 612954

sales@hotchkissairsupply.co.uk www.hotchkissairsupply.co.uk